

PLASTIC TECHNICAL MANUFACTURING FACTORY

Product Specification Sheet-Steel Pallet DESCRIPTION: 275 GALLON / 1000 LITER, UN, UV STABILIZED HDPE BOTTLE, DN 150 CAP 2" Plug with Vent, 2" Ball VALVE, Steel Pallet INTERMEDIATE BULK CONTAINER (IBC) GNX- IBC 1000Ltr- SP **Product Code** LENGTH: 1200 MM (+/-5 MM) X WIDTH: 1000 MM Dimensions (+/- 5 MM) HEIGHT: 1155 MM (+/- 5 MM) Tare Weight 56.5 KG +/- 5 % 1000 Litre Nominal Capacity: **Brimful Capacity:** 1060 Litre Galvanized Steel / Polyethylene high density Material 1200 Surface coated steel tubes with special features against extreme vibration stress.6/20 cage resistance welded with extra riveting at all the 20 joints on top horizontal bar along with all vertical members. Also two Restrain Bars are provided on top to support perfect stability. The cage is Outer container (Cage) replaceable. *Size 2 Label Plates, Corner Protector: 4 pieces, PE-HD, Black Grid / Label plate = Steel, galvanized against corrosion Rectangular blow molded inner tank of high density polyethylene nner container (PE-HD) with filling opening. Material PE-HD, UV stabilized natural white illing Opening DN 150 with external thread, closed with Black screw cap with 70mm plug Black seal cap. Screw-cap DN 150: PE-HD, Black O-ring gasket: Filling opening **EPDM** Material O-ring plug Yes with DG vent, Silicon-FDA Vent: Fitted with Ball valve DN 50 (2") with handle and safety guard. Butress thread on OD. Outlet sealed with an Al- lined PE-foil. Valve closed with Discharge opening Discharge valve-Body PE - Black PE - Black Discharge valve-cap Neack Gasket Material PE Ball Gasket PE Galvanized Steel, 4-way entry, easy way pallet. Pallet Steel Material Content of Lead, Cadmium, Mercury and Chromium below 100 Heavy metal ppm/weight, According EU-directive 94-62 EG content

31 HA1/Y/..

Printing / UN-marking